

TM

**COLUMBIA PETRO CHEM PVT. LTD.**

J-14,MIDC IND.AREA.TALOJA-410208

PH.022 7412735/7410816/FAX 7410276

TECHNICAL DATA SHEET**LIGHT WHITE OIL 12 TECHNICAL**

DATE : 05/04/2013

CONSIGNEE : VERUS

SR No	TEST PARAMETERS	TEST METHODS	SPECIFICATIONS		TYPICAL VALUE
			MIN	MAX	
1	Description	PHYSICAL	Bright & clears		Bright & clears
2	Colour , Saybolt	ASTM D- 156	+28 MIN	----	+30
3	Specific Gravity @ 25 ⁰ C	ASTM D 1298	0.815	0.860	0.824
4	Kinematic Viscosity @ 40 ⁰ C, cSt	ASTM D 445	10	14	12.2
5	Flash point, ⁰ C	ASTM D 92	150	----	160
6	Pour point, ⁰ C	ASTM D 97	---	-12	-15
7	Acid no. mg KOH/GM	ASTM D 974	----	0.1	0.0050
8	Copper corrosion@100 ⁰ C for 3 hrs	ASTM D 130	----	1b	1 a

Note -The above data is indicative of recent average values only.Minor variations,which do not affect Product performance or quality, may be expected in manufacture.

COLUMBIA PETRO CHEM PVT.LTD.

Technical/ QC Manager

Regd. Office: Triveni, 32nd Road , Bandra [W], Mumbai – 400 050; Ph.: 2646 2313/ 2915; Fax: 2646 3032

TM

**COLUMBIA PETRO CHEM PVT. LTD.**

J-14,MIDC IND.AREA.TALOJA-410208

PH.022 7412735/7410816/FAX 7410276

TECHNICAL DATA SHEET**LIGHT WHITE OIL 8 TECHNICAL**

DATE : 05/04/2013

CONSIGNEE : VERUS

SR No	TEST PARAMETERS	TEST METHODS	SPECIFICATIONS		TYPICAL VALUE
			MIN	MAX	
1	Description	PHYSICAL	Bright & clears		Bright & clears
2	Colour , Saybolt	ASTM D- 156	+28 MIN	---	+30
3	Specific Gravity @ 25 ⁰ C	ASTM D 1298	0.815	0.860	0.823
4	Kinematic Viscosity @ 40 ⁰ C, cSt	ASTM D 445	7.5	9.5	8.2
5	Flash point, ⁰ C	ASTM D 92	150	----	158
6	Pour point, ⁰ C	ASTM D 97	---	-12	-15
7	Acid no. mg KOH/GM	ASTM D 974	----	0.1	0.0048
8	Copper corrosion@100 ⁰ C for 3 hrs	ASTM D 130	----	1b	1 a

Note -The above data is indicative of recent average values only.Minor variations,which do not affect Product performance or quality, may be expected in manufacture.

COLUMBIA PETRO CHEM PVT.LTD.

Technical/ QC Manager

Regd. Office: Triveni, 32nd Road , Bandra [W], Mumbai – 400 050; Ph.: 2646 2313/ 2915; Fax: 2646 3032